

NASA TECH BRIEF

Marshall Space Flight Center



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

Digital Simulation Error Curves for a Spring-Mass-Damper System

The problem:

Reduce the excessive number of samples per cycle and the unnecessary iterations which increase cost and computation time on digital simulations of continuous data systems.

$A = \omega \left(\frac{1}{\zeta} \right)$ is the normalized integration gain.
 ω_D is the effective angular resonance frequency.
 ω_p is the programmed angular resonance frequency.
 ζ_p is the programmed damping ratio.
 T is the sampling interval in seconds.




Figure 1

The solution:

Plot the digital simulation errors for a spring-mass-damper system. Using these error curves, select the type of integration, the feedback update method, and the number of samples per cycle at resonance.

How it's done:

Block diagrams of a spring-mass-damper simulation and the preferred time advance update method are shown in Figure 1, where:

Z^{-1} is a transfer function for T seconds time delay.
 e^{TS} is a transfer function for T seconds time advance.
 $\frac{1}{K}$ is a constant for time advance update.
 I is the number of iterations for iteration update.
 X , \dot{X} , and \ddot{X} represent the mass displacement, velocity, and acceleration, respectively.
 S is the Laplace operator.
 N_R is the number of samples per cycle at resonance.

The effective damping ratio is: $\zeta_D \approx \zeta_p + \xi_R$

(continued overleaf)





Figure 2 Simpson's Integration

where ξ_R is the damping bias error. This error is plotted (Figure 2) for trapezoidal integration and Simpson's 1/3 formula, where N_R is the number of samples per cycle at resonance. Curves are shown for the iteration update method where $I = 1$, and for the time advance update method where $1/K = 0, 1/3$, and $1/2$.

The normalized resonance frequency, ω_D/ω_P , shown in Figure 3, is for trapezoidal integration and Simpson's 1/3 formula.

For the curves for trapezoidal integration, the time advance update method with $1/K = 1/3$ has smaller errors at 20 samples per cycle than the one-iteration update method at 30 samples per cycle. Thus, for the same accuracy, the time advance update method will solve the simulated problem in half the time of the one-iteration update method. This is based on an added time per iteration of $T/4$, i.e., one-quarter of the computation time without iteration.





Figure 3 Simpson's Integration

Note:

Requests for further information may be directed to:

Technology Utilization Officer
Marshall Space Flight Center
Code A&TS-TU
Huntsville, Alabama 35812
Reference: B71-10003

Patent status:

No patent action is contemplated by NASA.

Source: Lewis Alfred Knox of
International Business Machines Corp.
under contract to
Marshall Space Flight Center
(MFS-20770)